

## Внутренние настенные блоки

# AERI | AEVI | AEMI



AERI



AEVI



AEMI



Ionizer



Anti-corrosion protection – gold coating



Heating at temp. of -20 °C



3D DC Inverter



Wi-Fi ready



Mono and multi compatibility



Operating range up to -20 °C



Heating



Cooling



3D air flow



Wi-Fi ready



Mono and multi compatibility



Biofilter



Anti-corrosion protection – gold coating



3D DC Inverter



I Feel function



Automatic operating mode



Wi-Fi ready

### Внутренний блок

| Модель                                                 | ACP-07CH2IAEMI/I               | ACP-09CH25AERI/I+ R32 | ACP-12CH35AERI/I+ R32 | ACP-18CH50AERI/I+ R32 | ACP-12CH35AEVI/I2s R32 |
|--------------------------------------------------------|--------------------------------|-----------------------|-----------------------|-----------------------|------------------------|
| Мощность (Вт)                                          | 2052                           | 2638                  | 3517                  | 5275                  | 3517                   |
| Мощность (Вт)                                          | 2346                           | 2931                  | 3810                  | 5568                  | 3810                   |
| Расход воздуха (м³/ч) - высокий / средний / низкий     | 520 / 460 / 340                | 483 / 362 / 303       | 584 / 477 / 395       | 730 / 500 / 420       | 558 / 478 / 384        |
| Хладагент                                              | R32                            | R32                   | R32                   | R32                   | R32                    |
| Влагоудаление (л/ч)                                    | 1.0                            | 1.0                   | 1.2                   | 1.8                   | 1.2                    |
| Звуковое давление (дБ(A)) - высокий / средний / низкий | 40 / 30 / 26 / 21              | 42 / 35 / 25 / 21.5   | 42 / 35 / 25 / 22     | 43 / 38 / 33.5 / 28   | 37.5 / 32 / 30 / 24    |
| Звук в стандартных условиях (дБ)                       | ≤ 54                           | ≤ 56                  | ≤ 56                  | ≤ 57                  | ≤ 51                   |
| Размеры упаковки (мм)                                  | 870 x 270 x 360                | 875 x 285 x 375       | 875 x 285 x 375       | 1045 x 305 x 410      | 985 x 385 x 265        |
| Размеры устройства (мм)                                | 805 x 194 x 285                | 802 x 189 x 297       | 802 x 189 x 297       | 965 x 215 x 319       | 897 x 312 x 182        |
| Вес брутто/нетто (кг)                                  | 9.7 / 7.5                      | 11.1 / 8.6            | 11.1 / 8.6            | 14.2 / 10.9           | 14.2 / 10.5            |
| Диаметр трубки жидкости                                | 1/4"                           | 1/4"                  | 1/4"                  | 1/4"                  | 1/4"                   |
| Диаметр газовой трубки                                 | 3/8"                           | 3/8"                  | 3/8"                  | 1/2"                  | 3/8"                   |
| Кабель подключения питания (мм²)                       | 4 x 1.0                        | 4 x 1.0               | 4 x 1.0               | 4 x 1.0               | 5 x 1.5                |
| Электропитание                                         | ~220-240V/1/50Hz; наружн. блок |                       |                       |                       |                        |